



## SUBMITTAL DATA

# FSU36HP230V1R32AH 36000 BTU/H Floor Standing Unit Heat Pump System

Job Name	Location	Date
Purchaser	Engineer	
Submmited to	For	
Unit Designation	Schedule No.	
YBE1FB8F	FSU36HP230V1R32	2AH

#### **GENERAL FEATURES**

- AHRI Certificate: 215415558
- Quiet Operation and Multiple Fan Speed
- Swing Louver Control
- Multi-Directional Air Flow
- Wireless Remote with LCD Display Included
- Remote and Panel Control Option
- Low Ambient Cooling and Heating
- (Indoor and Outdoor) Copper Tube / Aluminum Fin
- Blue Colored Fin 500 Hrs Salt Spray Tested
- New R32 Refrigerant with Refrigerant Sensor

## SPECIFICATIONS, FEATURES & FUNCTION SUMMARY


INDOOR MODEL			FSU36HP230V1R32AH	FEATURES & FUNCTIONS SUMMARY	
System Type			HEAT PUMP		
Outdoor Model			LIV36HP230V1R32A0	SYSTEM FEATURES	
SYSTEM PERFORMAN	ICE			Inverter Type	G20 with Field Oriented control (FOC)
Caalian	Min - Max	Btu/h	25,837 - 45,216	Ultra Low Frequency Torque Control	Yes
Cooling	Capacity @95°F	Btu/h	33,600	Power Factor Correction	Yes
	Min - Max	Btu/h	18,175 - 37,092	Compressor Type - Inverter	High Efficiency Rotary
11 2	Capacity @47°F	Btu/h	34,000	Basepan With Electric Heater	Yes
Heating	Capacity @17°F	Btu/h	24,400	Indoor & Outdoor Fin Coating (Blue Fin)	Yes
	Capacity Max @5°F	Btu/h	24,400	Intelligent Defrosting	Yes
SEER2			20.0	Intelligent Preheating	Yes
EER2			12.00	Low Voltage Startup	Yes
HSPF2			8.5	Memory/Power Failure Recovery	Yes
COP @5°F			2.00	Self Diagnosis	Yes
COP @47°F			3.05	Wired Controller Interface	Yes
Cooling Temperature R	Range	°F	0 - 118	WiFi Included	No
Heating Temperature F		°F	-13 - 75	Indoor Fan Type	Centrifugal
Refrigerant Type			R32	Multi Fan Speeds	4 Speeds
INDOOR UNIT			FSU36HP230V1R32AH	Indoor Unit Display	Yes
		CFM		Auxilary Electrical Heater	No
Air flow (Min-Max)			883 - 1148	Ventilation (Outdoor Air)	No
Sound Pressure Level	(Min - Max)	dB(A)	48 - 54	REMOTE CONTROLLER FUNCTIONS	
Dehumidification		pt/hr	7.40	Auto Mode	Yes
External Dimensions (	(L x D x H)	in	23-7/64 × 15-33/64 × 74-6/64	Auto Clean	Yes
Package Dimension (L	x W x H)	in	28-10/64 × 18-32/64 × 83-42/64	Auto Fan	Yes
Net Weight		lbs	130.1	Auto Swing (Horizontal Auto Swing)	Yes
Gross Weight		lbs	156.6	Auto Swing - 180° (Vertical Auto Swing)	Yes
OUTDOOR UNIT			LIV36HP230V1R32A0	Clock	Yes
Sound Pressure Level		dB(A)	62	Dry Mode	Yes
External Dimensions (	(L x D x H)	in	39-3/8 x 15-13/16 x 29-3/8	Dry Anti-Mildew (X-Fan) Mode	Yes
Package Dimension (L	x W x H)	in	42-33/64 x 19-1/64 x 31-57/64		Yes
Net Weight		lbs	122.4	Energy Saving Mode	No
Gross Weight		lbs	133.4	Dirty Filter Alert	
REFRIGERANT PIPING	3			Fan Speed Control (7 Speeds)	Yes
Refrigerant Charge - R	410A	OZ	56.4		No
Additional Charge		oz/ft	0.4	Privacy Lock	Yes
Line Set Sized by Indo	or Unit (Liquid - Gas)	in	1/4 - 5/8	Quiet Mode	No
Line Set Size (Liquid -	Gas) - Flared	in	1/4 - 5/8	Intelligent Preheaing	Yes
Connections				Sleep Mode	Yes
Pre-Charge Length		ft	25	3 Sleep Mode Options	Yes
Pipe Length (Min - Max	x)	ft	10 - 131	Timer Mode	Yes
Max. Pipe Elevation		ft	82	Turbo Mode	Yes
ELECTRICAL				Display On/Off Control	Yes
Power Supply			208-230V / 1Ph / 60Hz (Powered by the Outdoor Unit)	Intelligent Defrosting  Power Failure Mode	Yes Yes
Voltage Range (Min - N	Max)	VAC	187 - 253	Fower Fallure Mode	res
Rated Current - Coolin	g	А	20		
Rated Current - Heatin	g	Α	20		
MCA		А	23		
MOCP		А	35		
Suggested Breaker Siz	ze	А	25		
Main Power Wire Size		AWG	Per Local Code		
Interconnecting Wire S	iize	AWG	14 / 4		
		,u	17 / 7		


## **DIMENSIONS**


## **INDOOR UNIT**

Unit: inch

FSU36HP230V1R32AH		
DIMENSIONS		
W	23 7/64	
Н	74 3/32	
D	15 33/64	










## **OUTDOOR UNIT**

Unit: inch

LIV36HP230V1R32A0			
DIMENSIONS			
Α	36 11/32		
В	39 3/8		
С	29 3/8		
D	14 17/32		
Е	16 13/16		
F	24 1/64		
G	15 35/64		








#### **CLEARANCES**

#### **INDOOR UNIT**

#### Minimum clearence


DIMENSIONS		
А	60	
В	12	
С	39	
D	6	
Е	90	

Unit: inch




## **OUTDOOR UNIT**

Minimum clearence



### NOTE:

If bottom of the unit is free of airflow obstructions similar to the mounting bracket figure, the clearance to the wall on the back can be reduced to 3 inches.





Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.